

Sylproof Tubular LED - Microwave sensor DALI

Sylproof Tubular LED 1X1200 DALI MW NW
0047623



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X1200 DALI MW NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	2734
Luminous flux (lm)	2734
Luminaire efficacy (lm/W)	106.79
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	25.6
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476230


PHOTOMETRY

Sylproof Tubular LED - Microwave sensor DALI *Sylproof Tubular LED 1X1200 DALI MW NW* 0047623

Distance [m]	Cone diameter [m]	E0°	E15°	E30°	E45°	E60°	E75°	E90°	Iluminance [lx]
0.5	1.17 1.60	3375	482	146	84	54	34	22	
1.0	2.34 3.20	844	116	49	31	20	13	8	
1.5	3.51 4.80	375	51	22	14	9	6	4	
2.0	4.68 6.40	211	29	12	8	5	3	2	
2.5	5.85 8.00	135	19	8	5	3	2	1	
3.0	7.02 9.60	84	12	5	3	2	1	1	

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 12.5°)
 — C90 - C270 (Half beam angle: 99.0°)



TECHNICAL DRAWINGS

