

## Insaver LED II 150

*Insaver LED II 150 High Output WW EB*

3098114



### Product features

- Circular LED downlight with up to 114lm/W efficacy and 2,400 luminaire lumen output. Innovative easy installation system allows for a rapid, single point installation. For 150mm cut outs. IP44 or UGR<19 compliant with additional accessories. 3 hour emergency and surface mounted versions available. Plus3 version includes Wieland GST connector.




### PRODUCT OVERVIEW

Product name	Insaver LED II 150 High Output WW EB
Technology	LED
Housing	AGC (advanced graphite composite)
Mount	Ceiling recessed mounting
Environment	Internal
General application	Office
ETIM Class	EC001744
E-number FI	4271291
E-number SE	7464707
Warranty	5 years
Fixture luminous flux (lm)	2088
Luminaire efficacy (lm/W)	95
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	76
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	22
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP23
IK rating	IK02
Product EAN number	8711971981145

### PHOTOMETRY

## Insaver LED II 150 Insaver LED II 150 High Output WW EB 3098114



### TECHNICAL DRAWINGS

