

HSI-TD Hsi-Td150w/Ndl Uvs Rx7s Slv 0020233

Product features







PRODUCT OVERVIEW

| Product name | Hsi-Td150w/Ndl Uvs Rx7s Slv |
|----------------------------|---|
| Technology | HID |
| Watt (Rated) (W) | 150 |
| Туре | HSI-TD |
| Cap/Base | RX7s-24 |
| Lamp finish | Clear |
| Fixture rating | Enclosed |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail |
| ETIM Class | EC000037 |
| Luminous flux (Im) | 12500 |
| Colour temperature (K) | 4200 |
| CRI (Ra) | 80 |
| Wattage (W) | 150 |
| Product Voltage (V) | 95 |
| Average life (Nominal) (h) | 12000 |
| Product EAN number | 5410288202334 |

DATA TABLE

| General data | |
|----------------------------|---|
| Product name | Hsi-Td150w/Ndl Uvs Rx7s Slv |
| Technology | HID |
| Watt (Rated) (W) | 150 |
| Туре | HSI-TD |
| Cap/Base | RX7s-24 |
| Lamp finish | Clear |
| Fixture rating | Enclosed |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail |
| ETIM Class | EC000037 |
| Optical data | |
| Luminous flux (Im) | 12500 |
| Luminous flux (Rated) (Im) | 12500 |



HSI-TD Hsi-Td150w/Ndl Uvs Rx7s Slv 0020233

| Ambient temperature for maximum | 0.5 |
|---|----------------|
| luminous flux (°C) | 25 |
| ` ' | 4200 |
| CRI (Ra) | 80 |
| Adjustable chromaticity | N |
| Rated lumen maint. factor (%) at 4000 h 50Hz | 82 |
| Rated lumen maint. factor (%) at 6000 h 50Hz | 80 |
| Rated lumen maint. factor (%) at 8000 h 50Hz | 79 |
| Rated lumen maint. factor (%) at 12000 h 50Hz | 76 |
| Electrical data | |
| Wattage (W) | 150 |
| | 1.8 |
| Product Voltage (V) | 95 |
| Control gear required | Yes |
| | No |
| kWh per 1000 hours burning time | 165 |
| | |
| Lifetime data | |
| | 12000 |
| | 12000 |
| | 8000 |
| | 100 |
| ` , | 100 |
| | 97 |
| · · · · · · · · · · · · · · · · · · · | 90 |
| 50Hz | 50 |
| Rated survival factor (%) at 16000 h 50Hz | 70 |
| Physical data | |
| Max. Lamp Diameter (mm) - D | 25 |
| , | 0.029 |
| Packaging | |
| Single packaging type | Carton |
| | 5410288202334 |
| | 20.0 |
| | 3.5 |
| | 3.5 |
| | 15410288202331 |
| ` , | 10 |
| | 20.5 |
| Packaging inner width (cm) | 18.6 |
| | 7.9 |
| Packaging inner depth (cm) | 7.0 |



HSI-TD Hsi-Td150w/Ndl Uvs Rx7s Slv 0020233

| Units per outer package | 120 |
|--|------------|
| Packaging outer length / height (cm) | 49.8 |
| Packaging outer width (cm) | 39.5 |
| Packaging outer depth (cm) | 23.4 |
| Safety data | |
| Lamp mercury content (mg) | 9.00 |
| Breakage cleaning instructions | Applicable |
| Recommendation for disposal at end of life | Applicable |
| Special purpose lamp | No |

No

TECHNICAL DRAWINGS

Suitable for household illumination

