

Hydroproof LED G3 fixed output HYDROPROOF LED G3 600mm Twin 4K 0048770



Product features

- Hydroproof, integrated LED chemical resistant weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. GRP housing, PMMA diffuser, Non dimmable, 4000K, CRI80, 2800 lm, 19 W, 145 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK02, IP65.



PRODUCT OVERVIEW

Product name	HYDROPROOF LED G3 600mm Twin 4K
Technology	LED
Housing	Polyester
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4306978
Warranty	5 years
Fixture luminous flux (lm)	2800
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	19
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Grey
IP rating	IP65
IK rating	IK02
Product EAN number	5410288487700

DATA TABLE

General data

Product name	HYDROPROOF LED G3 600mm Twin 4K
Technology	LED
Housing	Polyester
Mount	Ceiling surface mounting

Hydroproof LED G3 fixed output *HYDROPROOF LED G3 600mm Twin 4K* 0048770

General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4306978
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2800
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	19
Mains voltage (V)	220-240V~
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Mains frequency (Hz)	50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Drive current (mA)	300
Inrush Current (A)	4
Inrush Duration (µs)	32
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	70
Max. Luminaires per 13A C Breaker	90
Max. Luminaires per 16A C Breaker	110
Max. Luminaires per 20A C Breaker	140
Max. Luminaires per 10A B Breaker	60
Max. Luminaires per 13A B Breaker	80
Max. Luminaires per 16A B Breaker	100
Max. Luminaires per 20A B Breaker	125

Lifetime data

Lifespan L70 B50	60000
Lifespan L80 B10	60000
Lifespan L90 B50	60000

Physical data

Housing colour	Grey
----------------	------

Hydroproof LED G3 fixed output HYDROPROOF LED G3 600mm Twin 4K 0048770

IP rating	IP65
IK rating	IK02
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	665
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78
Weight (kg)	1.18

Packaging

Single packaging type	Carton
Product EAN number	5410288487700
Packaging single length / height (cm)	77.5
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288487700
Units per outer package	1
Packaging outer length / height (cm)	77.5
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4


Safety data

Optimal operating condition (°C)	-20-40
Dry applications use only	No

PHOTOMETRY

Distance [m]	Cone diameter [m]	E ₀ ^(°)	E ₁ (C90)	E ₁ (C0)
0.5	1.21 1.48	3575	464	314
1.0	2.42 2.97	896	116	79
1.5	3.63 4.45	398	52	35
2.0	4.84 5.93	224	29	21
2.5	6.04 7.41	143	19	13
3.0	7.25 8.90	99	13	9

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 112.0°)
 — C90 - C270 (Half beam angle: 100.8°)



TECHNICAL DRAWINGS

