

RefLED Retro Superia ES50 DIMMABLE REFLED SUPERIA RETRO ES50 580LM DIM 840 36° SL 0029972



Product features

 Premium performance professional LED GU10 range with the same look and feel of traditional halogen GU10 lamp• Recreates backlight effect similar to halogen dichroic lamps• Full glass design means no colours clashing between lamp and fixture• Very long lifetime of up to 25,000 hours• COOLFIT functionality - ensures overheat and over temperature protection• High switching cycles: >100,000• High colour rendering: CRI80• Dimmable on approved dimmers.• Warranty: 5 Years



PRODUCT OVERVIEW

Product name	REFLED SUPERIA RETRO ES50 580LM DIM 840 36° SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number Fl	4740704
E-number SE	8294396
Warranty	5 years
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	36
Wattage (W)	6.5
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288299723

DATA TABLE

General data	
Product name	REFLED SUPERIA RETRO ES50 580LM DIM 840 36° SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail

SYLVANIA

RefLED Retro Superia ES50 DIMMABLE REFLED SUPERIA RETRO ES50 580LM DIM 840 36° SL 0029972

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740704
E-number SE	8294396
Warranty	5 years
Optical data	
Rated Luminous Flux Useful (Im)	580
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Rated Luminous Intensity (cd)	1080
Beam Angle (°)	36
Electrical data	
Wattage (W)	6.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.7
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
kWh per 1000 hours burning time	7
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
	20000
Physical data	
Nominal Product Length (mm)	54
Nominal Product Length (mm)	50
Weight (kg)	0.058
Packaging	
Single packaging type	Carton
Product EAN number	5410288299723
Packaging single length / height (cm)	5.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	6.7
DUN14 (inner)	25410288299727
Units per inner package	6
Packaging inner length / height (cm)	11.0
Packaging inner width (cm)	16.4
Packaging inner depth (cm)	9.1



RefLED Retro Superia ES50 DIMMABLE REFLED SUPERIA RETRO ES50 580LM DIM 840 36° SL 0029972

DUN14 (outer)	15410288299720
Units per outer package	60
Packaging outer length / height (cm)	58.6
Packaging outer width (cm)	18.6
Packaging outer depth (cm)	20.2
Safety data	
Safety data Breakage cleaning instructions	Not applicable
	Not applicable No
Breakage cleaning instructions	••
Breakage cleaning instructions Special purpose lamp	No
Breakage cleaning instructions Special purpose lamp Dry applications use only	No Yes