

Giotto surface accessories Giotto LED 200 Surface 4000K Numberlight 3032813



Product features

Ambient and decorative square LED bulkhead. Perfect for 1x16W TC-DD replacement. White robust polycarbonate body with opal diffuser. 684LM. 16W. 43lm/W. 4000K. Drive current: 700mA. CRI 80. Non-dimmable electronic driver. IP44. IK10. 50,000 hrs (L70). (HxWxD) 200x200x140mm. 5 step MacAdam ellipse. Class 1. 220-240V. Energy class: A++, A+, A.













PRODUCT OVERVIEW

Product name	Giotto LED 200 Surface 4000K Numberlight
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Internal/External
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC002892
E-number FI	4270176
E-number SE	7535070
Fixture luminous flux (lm)	684
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	75
Photobiological Risk Group	RG0
Total power consumption (W)	16
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP44
IK rating	IK10
Product EAN number	8711971328131

DATA TABLE

General data	
Product name	Giotto LED 200 Surface 4000K Numberlight
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Internal/External
General application	Hospitality, Logistics & Industry, Residential & Consumer




Giotto surface accessories Giotto LED 200 Surface 4000K Numberlight 3032813

ETIM OF	F000000
ETIM Class	EC002892
E-number FI	4270176
E-number SE	7535070
Ontinal data	
Optical data	
Fixture luminous flux (lm)	684
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	75
Adjustable chromaticity	N
Distribution type	Symmetric, Direct
Photobiological Risk Group	RG0
Electrical data	
Total power consumption (W)	16
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear type	Electronic ballast
Transformer required	Yes
Drive current (mA)	700
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60/HF
, , ,	
Physical data	
Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	200
Nominal Product Width (mm)	200
Nominal Product Height (mm)	140
Weight (kg)	0.89
Packaging	
Single packaging type	Carton
Product EAN number	8711971328131
Packaging single length / height (cm)	26.5
Packaging single width (cm)	26.5
Packaging single depth (cm)	9.5
Units per outer package	1
Packaging outer length / height (cm)	26.5
	26.5
Packaging outer width (cm)	
Packaging outer depth (cm)	9.5

PHOTOMETRY



Giotto surface accessories Giotto LED 200 Surface 4000K Numberlight 3032813



TECHNICAL DRAWINGS

