

CurveLyte

CURVELYTE 1265x330 HO D/I 3K DALI BLACK
2093175



Product features

- CURVELYTE 1265x330 HO D/I 3K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution. Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Warm White (3000K) LED Colour Temperature, 6250lm, 55W, 114lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



PRODUCT OVERVIEW

Product name	CURVELYTE 1265x330 HO D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260864
Warranty	5 years
Fixture luminous flux (lm)	6250
Luminaire efficacy (lm/W)	114
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Housing colour	Black
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931750

DATA TABLE

General data

Product name	CURVELYTE 1265x330 HO D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office

CurveLyte

CURVELYTE 1265x330 HO D/I 3K DALI BLACK
2093175

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001743
E-number FI	4260864
Warranty	5 years

Optical data

Fixture luminous flux (lm)	6250
Luminaire efficacy (lm/W)	114
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	55
Mains voltage (V)	230V~
Electrical protection	Class I
Drive current (mA)	1200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lifespan L70 B50	161000
Lifespan L80 B20	49000

Physical data

Housing colour	Black
IP rating	IP20
IK rating	IK06
Nominal Product Length (mm)	1265
Nominal Product Width (mm)	336
Nominal Product Height (mm)	46
Weight (kg)	5.8

Packaging

Single packaging type	Carton
Product EAN number	5025768931750
Packaging single length / height (cm)	135.0
Packaging single width (cm)	41.0
Packaging single depth (cm)	16.5
DUN14 (outer)	05025768931750
Units per outer package	1
Packaging outer length / height (cm)	135.0
Packaging outer width (cm)	41.0
Packaging outer depth (cm)	16.5


CurveLyte *CURVELYTE 1265x330 HO D/I 3K DALI BLACK* 2093175

PHOTOMETRY

0.5	2.09 3.19	E(0°) E(C90) E(C180)	4524 183 90
1.0	4.17 6.38	E(0°) E(C90) E(C180)	1131 46 15
1.5	6.26 9.57	E(0°) E(C90) E(C180)	503 20 7
2.0	8.35 12.76	E(0°) E(C90) E(C180)	283 11 4
2.5	10.44 15.96	E(0°) E(C90) E(C180)	181 7 2
3.0	12.52 19.15	E(0°) E(C90) E(C180)	128 5 2

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 145.2°)
 — C90 - C270 (Half beam angle: 128.8°)



TECHNICAL DRAWINGS

