

CurveLyte

CURVELYTE 1265x330 HO D/I 3K DALI BLACK
2093175



Product features

- CURVELYTE 1265x330 HO D/I 3K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution. Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Warm White (3000K) LED Colour Temperature, 6250lm, 55W, 114lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



PRODUCT OVERVIEW

Product name	CURVELYTE 1265x330 HO D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260864
Warranty	5 years
Fixture luminous flux (lm)	6250
Luminaire efficacy (lm/W)	114
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Housing colour	Black
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931750


PHOTOMETRY

CurveLyte *CURVELYTE 1265x330 HO D/I 3K DALI BLACK* 2093175

0.5	2.09	E:07	4824
	3.19	E:09 E:10	183 80
1.0	4.17	E:07	1101
	6.33	E:09 E:10	46 19
1.5	6.26	E:07	802
	9.57	E:09 E:10	37 7
2.0	8.35	E:07	382
	12.76	E:09 E:10	11 4
2.5	10.44	E:07	181
	15.66	E:09 E:10	2 2
3.0	12.52	E:07	105
	19.15	E:09 E:10	5 2

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 145.8°)
 — C90 - C270 (Half beam angle: 128.8°)



TECHNICAL DRAWINGS

