

Signo 155 LED *SIGNO 155 LED HO 40W WW WH* 3040051



Product features

Recessed Adjustable Accent Downlight, integrated LED, die cast aluminium body, Ø155mm cut-out, 140mm recess depth, 355° rotation, 60° tilt, 3500lm, 40W, 88lm/W, 3000K, CRI 80, 36° beam, aluminium reflector, non-dimmable, electronic driver included, drive current 1000mA, Class II, IP20, IK02, 50000hours (L70B50), Ø167x140mm




PRODUCT OVERVIEW


Product name	SIGNO 155 LED HO 40W WW WH
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Internal
General application	Retail
ETIM Class	EC001744
E-number FI	4270024
Warranty	5 years
Fixture luminous flux (Im)	3500
Luminaire efficacy (Im/W)	88
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	4
Beam Angle (°)	36
Photobiological Risk Group	RG2
Total power consumption (W)	40
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	8711971400516

PHOTOMETRY



Signo 155 LED SIGNO 155 LED HO 40W WW WH 3040051





TECHNICAL DRAWINGS

