

## Sylproof Tubular LED - DALI

*Sylproof Tubular LED 1X1200 DALI WW*  
0047605



### Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



### PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X1200 DALI WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	2629
Luminous flux (lm)	2629
Luminaire efficacy (lm/W)	102.69
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	26
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476056

### PHOTOMETRY


## Sylproof Tubular LED - DALI

Sylproof Tubular LED 1X1200 DALI WW  
0047605

0.5	1.17	E:0°	324
	1.60	E:C90	445
		E:C0	347
1.0	2.34	E:0°	211
	3.59	E:C90	311
		E:C0	217
1.5	3.51	E:0°	161
	5.38	E:C90	230
		E:C0	171
2.0	4.68	E:0°	120
	7.15	E:C90	175
		E:C0	131
2.5	5.96	E:0°	90
	8.96	E:C90	130
		E:C0	97
3.0	7.03	E:0°	80
	10.73	E:C90	115
		E:C0	85

Distance [m]      Core diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 12.5°)  
— C90 - C270 (Half beam angle: 99.0°)



## TECHNICAL DRAWINGS

