

Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH NW DIMMABLE 3079453



Product features

25° tiltable, IP23 (from the front) Accent downlight perfect for 50W Halogen retrofits. Optimal solution in size and luminous efficiency for hospitality and accent and display lighting applications with a 36° beam and 515 lumen output. The downlight provides 4000K CCT and also comes including a dimmable driver.

















PRODUCT OVERVIEW

Product name	INST ECO KIT LED ADJ WH NW DIMMABLE
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
ETIM Class	EC001744
E-number FI	4271081
E-number SE	7475323
Fixture luminous flux (lm)	515
Luminaire efficacy (lm/W)	51.5
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	83
Colour Consistency (SDCM)	5
Beam Angle (°)	36
Total power consumption (W)	10
Electrical protection	Class II
Control gear type	Electronic ballast
Minimum dimming level (%)	70
Housing colour	White
IP rating	IP23/20
IK rating	IK02
Product EAN number	8711971794530

DATA TABLE

General data	
Product name	INST ECO KIT LED ADJ WH NW DIMMABLE
Technology	LED
Housing	Aluminium



Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH NW DIMMABLE 3079453


Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4271081
E-number SE	7475323
Optical data	
Fixture luminous flux (Im)	515
Luminaire efficacy (lm/W)	51.5
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	83
Colour Consistency (SDCM)	5
Adjustable chromaticity	N
Beam Angle (°)	36
Distribution type	Direct
Electrical data	
Total power consumption (W)	10
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear type	Electronic ballast
Transformer required	Yes
Minimum dimming level (%)	70
Drive current (mA)	800
Physical data	
Housing colour	White
IP rating	IP23/20
IK rating	IK02
Diffuser finish	Transparent
Diffuser material	Other
Nominal Product Length (mm)	78
Nominal Product Width (mm)	78
Nominal Product Height (mm)	62
Nominal Product Diameter (mm)	78
Cutout Dimensions (W x L in mm or Diameter in mm)	68
Weight (kg)	0.352
Recessed Depth (mm)	110
Packaging	
Single packaging type	Carton
Product EAN number	8711971794530
Packaging single length / height (cm)	15.3
Packaging single width (cm)	11.2
. acraging onigio mani (oni)	



Instar Eco Kit LED Adjustable - Dimmable INST ECO KIT LED ADJ WH NW DIMMABLE 3079453

Packaging single depth (cm)	9.0
DUN14 (outer)	18711971794537
Units per outer package	20
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	24.0
Packaging outer depth (cm)	47.0

PHOTOMETRY



TECHNICAL DRAWINGS

