

Sylproof Superia LED G3 MW

SYLPROOF SUPERIA LED G3 1500mm Single 4K QC DALI MW
0048754



Product features

- Sylproof Superia, integrated LED weatherproof luminaire with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. L 1578 mm x W 84 mm x H 75 mm size, Polycarbonate housing, Polycarbonate diffuser, DALI dimmable, with MW sensor, 4000K, CRI80, 4800 lm, 32 W, 150 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.



PRODUCT OVERVIEW


Product name	SYLPROOF SUPERIA LED G3 1500mm Single 4K QC DALI MW
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	4800
Luminaire efficacy (lm/W)	150
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	32
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487540

PHOTOMETRY

Sylproof Superia LED G3 MW

SYLPROOF SUPERIA LED G3 1500mm Single 4K QC DALI MW

0048754



Distance [m]	Cone diameter [m]	E0%	E10%	E30%	E50%	E70%	E90%	Beam diameter [m]	Illuminance [lx]
0.5	1.41 1.38	50%	54.8°	54.1°	54.1°	54.1°	54.1°	995	641
1.0	2.81 2.76	50%	54.8°	54.1°	54.1°	54.1°	54.1°	168	167
1.5	4.22 4.14	50%	54.8°	54.1°	54.1°	54.1°	54.1°	73	74
2.0	5.63 5.53	50%	54.8°	54.1°	54.1°	54.1°	54.1°	41	42
2.5	7.04 6.91	50%	54.8°	54.1°	54.1°	54.1°	54.1°	26	27
3.0	8.44 8.29	50%	54.8°	54.1°	54.1°	54.1°	54.1°	19	19

Distance [m] Cone diameter [m]

— C0 - C180 (Half beam angle: 180.0°)

— C90 - C270 (Half beam angle: 109.2°)

Illuminance [lx]

TECHNICAL DRAWINGS

