

## SylBatten LED

SYLBATTEN LED 1505MM 4000LM 6000K EB (TP3)

0045186



### Product features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing (safety cable included), through wiring capability (TP3 = 3 core), sheet steel, 4377LM, 39W, 112m/W, 6000K, drive current: 350mA, CRI 80, 138° wide beam angle, electronic driver (non dimmable), IP20, IK07, 50,000 hrs (L70), (LxWxH) 1505x66x76mm, 5 step MacAdam ellipse, 3.7kg, white RAL 9016, Class 1, 220-240V, energy class: A++, A+, A.



### PRODUCT OVERVIEW






Product name	SYLBATTEN LED 1505MM 4000LM 6000K EB (TP3)
Technology	LED
Housing	Steel
Mount	Ceiling surface mounting
Environment	Internal
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4274260
Fixture luminous flux (lm)	4377
Luminaire efficacy (lm/W)	112.23
LOR (%)	100
Colour temperature (K)	6000
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Beam Angle (°)	138
Glare control	< 30
Photobiological Risk Group	RG0
Total power consumption (W)	39
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Built-in
Dimmable	No
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288451862

### PHOTOMETRY

## SylBatten LED

SYLBATTEN LED 1505MM 4000LM 6000K EB (TP3)

0045186



## TECHNICAL DRAWINGS



Version	L	H1	W1
600mm	605	90	130
1000mm	1005	90	130
1500mm	1505	90	130
1500mm PRL	1505	90	130
1500mm PRL	1805	90	130



Version	L	H	W
600mm	600	70	90
1000mm	1000	70	90
1500mm	1500	70	90
1000mm PRL	1000	70	90
1500mm PRL	1505	70	90