


Start Surface IP66 Ø350mm START SURFACE IP66 1450LM 830 IK10 BLK 0049002



Product features

- LED exterior surface mounted luminaire, 350mm diameter, 1450lm as max. lumen output, can be adjusted down to 700lm by internal switch, 14,5W power consumption max., 97lm/W efficacy, 3000K color temperature, CRI80, non-dimmable, IP66, IK10, 50,000 hours (L70), black housing, vandal resistant




PRODUCT OVERVIEW

Product name	START SURFACE IP66 1450LM 830 IK10 BLK
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Environment	Indoor, Outdoor
General application	Hospitality
ETIM Class	EC002892
E-number FI	4579480
Warranty	5 years
Fixture luminous flux (lm)	1450
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	14.5
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9011 - Graphite black
IP rating	IP66
IK rating	IK10
Product EAN number	5410288490021

PHOTOMETRY

Start Surface IP66 Ø350mm *START SURFACE IP66 1450LM 830 IK10 BLK* 0049002



TECHNICAL DRAWINGS

