


Syl-Line electrical unit SYL-LINE GT3R 4K WD WH EM 0042117



Product features

- Syl-Line LED Gear Tray, 4000K Neutral White, Non Dimming, Wide Beam, White, 3 hour Maintained Emergency




PRODUCT OVERVIEW

Product name	SYL-LINE GT3R 4K WD WH EM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
Environment	Interior
General application	Logistics & Industry, Retail
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	6342
Luminous flux (lm)	6342
Luminaire efficacy (lm/W)	118
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0
Total power consumption (W)	54
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288421179


PHOTOMETRY

Syl-Line electrical unit SYL-LINE GT3R 4K WD WH EM 0042117



Distance [m]	Cone diameter [m]	E107	E109	E110	Illuminance [lx]
0.5	0.96 0.96	1082	2030	1977	
1.0	1.96 1.97	278	502	494	
1.5	2.94 2.96	127	222	220	
2.0	3.92 3.94	68	125	121	
2.5	4.90 4.93	48	80	79	
3.0	5.88 5.92	35	58	57	

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 81.2°)
C90 - C270 (Half beam angle: 88.8°)



Distance [m]	Cone diameter [m]	E107	E109	E110	Illuminance [lx]
0.5	1.01 1.02	1058	174	174	
1.0	2.02 2.04	261	44	43	
1.5	3.03 3.05	112	20	19	
2.0	4.04 4.07	63	11	11	
2.5	5.05 5.08	40	7	7	
3.0	6.06 6.11	28	5	5	

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 81.2°)
C90 - C270 (Half beam angle: 88.8°)

TECHNICAL DRAWINGS

