

ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HE 4FT 2200LM 830
0029504



Product features

- 60,000 hours average rated lifetime (L70 F50).
- Last 3 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp.
- High switching cycles - 200,000X.
- High lumen efficacy -138lm/W.
- Omni-directional light distribution and wide beam angle.
- Minimum and maximum operating temperature: -20°C to 50°C.
- Glass construction and polycarbonate end-caps.
- Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast.
- Works only with compatible electronic ballasts.
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HE 4FT 2200LM 830
Technology	LED
Watt (Rated) (W)	16
General application	Office, Hospitality, Logistics & Industry, Retail, Residential & Consumer, Museums & Galleries, Education
ETIM Class	EC001959
E-number FI	4740601
E-number SE	8293574
Warranty	5 years
Luminous flux (lm)	2200
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	16
Product Voltage (V)	80
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295046

TECHNICAL DRAWINGS

