

Sylproof Superia LED G3 DALI

SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI
0048737



Product features

- Sylproof Superia, integrated LED weatherproof luminaire with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. GRP housing, Polycarbonate diffuser, DALI dimmable, 4000K, CRI80, 2700 lm, 19 W, 140 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.




PRODUCT OVERVIEW

Product name	SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI
Technology	LED
Housing	Polyester
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	2700
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	19
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487373

PHOTOMETRY

Sylproof Superia LED G3 DALI SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI 0048737



0.5	1.17	E(0°)	333*
	1.52	E(C90)	451*
1.0	2.35	E(0°)	647*
	3.04	E(C90)	115*
1.5	3.52	E(0°)	378*
	4.97	E(C90)	51*
2.0	4.70	E(0°)	212*
	6.09	E(C90)	29*
2.5	5.87	E(0°)	158*
	7.61	E(C90)	19*
3.0	7.05	E(0°)	94*
	9.13	E(C90)	13*

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 113.4°)
 — C90 - C270 (Half beam angle: 99.2°)

TECHNICAL DRAWINGS

