

Lynx T

LYNX-T 26W/830 GX24D-3 SLV
0027811



Product features

- Triple bend compact pin-base lamps, - Suitable for operation on Magnetic control gear, - Excellent colour rendering



PRODUCT OVERVIEW

Product name	LYNX-T 26W/830 GX24D-3 SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	Other
Type	Lynx T
Cap/Base	GX24d-3
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944063
E-number SE	8357413
E-number Norway	3825355
Luminous flux (lm)	1800
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	82
Wattage (W)	26
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288278117

DATA TABLE

General data

Product name	LYNX-T 26W/830 GX24D-3 SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	Other
Type	Lynx T
Cap/Base	GX24d-3
Lamp finish	Frosted/Coated

Lynx T

LYNX-T 26W/830 GX24D-3 SLV
0027811

Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944063
E-number SE	8357413
E-number Norway	3825355

Optical data

Luminous flux (lm)	1800
Luminous flux (Rated) (lm)	1800
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	66
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 8000 h 50Hz	75
Rated lumen maint. factor (%) at 16000 h 50Hz	78
Rated lumen maint. factor (%) at 20000 h 50Hz	75

Electrical data

Wattage (W)	26
Starting time (max) (s)	10 Sec
Current (A)	0.325
Product Voltage (V)	220
Ignition voltage (V)	194
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	26

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72

Lynx T

L YNX-T 26W/830 GX24D-3 SLV

0027811

Rated survival factor (%) at 12000 h 50Hz	50
Rated survival factor (%) at 16000 h 50Hz	60
Rated survival factor (%) at 20000 h 50Hz	25

Physical data

Max. Length base to base (mm) - A	148
Max. Lamp Diameter (mm) - D	49
Weight (kg)	0.082

Packaging

Single packaging type	Carton
Product EAN number	5410288278117
Packaging single length / height (cm)	4.8
Packaging single width (cm)	4.8
Packaging single depth (cm)	13.6
DUN14 (outer)	15410288278114
Units per outer package	10
Packaging outer length / height (cm)	26.4
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	14.2

Safety data

Lamp mercury content (mg)	2.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes

TECHNICAL DRAWINGS

