Beacon LED Projector - Gobo

Beacon Muse Gobo Projector O/B 3000K Three Circuit Track - White 2055179



Product features

Beacon Projector offers precision light exactly where it is needed. The Gobo Projector with the use of ROSCO filters allow you to project a still image printed/cut/lasered onto a specially made glass/metal/acetate filter - for example a company logo, text, shapes, images. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.















PRODUCT OVERVIEW

Product name	Beacon Muse Gobo Projector O/B 3000K Three Circuit Track - White
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	-
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Beam Angle (°)	10
Photobiological Risk Group	RG1
Total power consumption (W)	26
Product Voltage (V)	240
Electrical protection	Class I
Control gear mounting	Integral
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768551798
Light source included	INTEGRATED LED

DATA TABLE

General data	
Product name	Beacon Muse Gobo Projector O/B 3000K Three Circuit Track - White
Technology	LED
Housing	Aluminium
Mount	Track mounting



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 3000K Three Circuit Track - White 2055179

	Laboration of the control of the con
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	-
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	95
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam Angle (°)	10
Distribution type	Adjustable
Photobiological Risk Group	RG1
•	
Electrical data	
Total power consumption (W)	26
Mains voltage (V)	230V~
Product Voltage (V)	240
Electrical protection	Class I
-	Integral
Control dear mounting	
Control gear mounting Transformer required	Yes
Control gear mounting Transformer required Nominal Frequency (Hz) Lifetime data	
Transformer required Nominal Frequency (Hz)	Yes
Transformer required Nominal Frequency (Hz) Lifetime data	Yes 50/60Hz
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data	Yes 50/60Hz
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour	Yes 50/60Hz 50000
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating	Yes 50/60Hz 50000 White
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating	Yes 50/60Hz 50000 White IP20
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm)	Yes 50/60Hz 50000 White IP20 IK02
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating	Yes 50/60Hz 50000 White IP20 IK02 185
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm)	Yes 50/60Hz 50000 White IP20 IK02 185 215
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type	Yes 50/60Hz 500/60Hz 50000 White IP20 IK02 185 215 80 1.365
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5 13.0
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5 13.0 05025768551798
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5 13.0 05025768551798 1
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5 13.0 05025768551798 1 32.0
Transformer required Nominal Frequency (Hz) Lifetime data Lifespan L70 B50 Physical data Housing colour IP rating IK rating Nominal Product Width (mm) Nominal Product Height (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	Yes 50/60Hz 50000 White IP20 IK02 185 215 80 1.365 Carton 5025768551798 32.0 15.5 13.0 05025768551798 1



Beacon LED Projector - Gobo Beacon Muse Gobo Projector O/B 3000K Three Circuit Track - White 2055179

TECHNICAL DRAWINGS

