

START eco Downlight 5in1 55-175 PIR

START eco Downlight 5in1 55-175 2000LM PIR

0053394



Product features

- START eco Downlight 5in1 is an integrated LED recessed / surface mounted downlight with built in non dimmable driver and PIR sensor. PIR sensor with time settings (3 min max) and adjustable daylight lux level. Colour temperature (3000K, 4000K and 6500K) can be chosen by a 3-way switch located on the back of the fixture. Adaptability to various cut-outs from 55mm to 175mm. 21W, 2000lm, 95lm/W.









PRODUCT OVERVIEW

Product name	START eco Downlight 5in1 55-175 2000LM PIR
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4278104
Warranty	3 years
Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	95
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK03
Product EAN number	5410288533940

PHOTOMETRY

START eco Downlight 5in1 55-175 PIR

START eco Downlight 5in1 55-175 2000LM PIR
0053394



TECHNICAL DRAWINGS

