

Global Trac Pro GLOBAL TRAC PRO 4M BLACK XTS4400-2



Product features

- Global Trac Pro - 3 Circuit Track, circuits can be controlled individually, aluminium body, suitable for surface mounting, 4000 x 31.5 x 32.5 mm (L x W x H), 3.642 kg, black (RAL 9005).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PRO 4M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC000101
E-number SE	7402249
Warranty	5 years
Light colour	N/A
Dimmable	No
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014506049

DATA TABLE

General data

Product name	GLOBAL TRAC PRO 4M BLACK
Technology	Accessory
Housing	Aluminium
General application	Retail
Operating temperature range (°C)	0°C - 25°C
ETIM Class	EC000101
E-number SE	7402249
Warranty	5 years

Optical data

Light colour	N/A
--------------	-----

Electrical data

Mains voltage (V)	220-240V~
Dimmable	No

Global Trac Pro GLOBAL TRAC PRO 4M BLACK XTS4400-2

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	4000
Nominal Product Width (mm)	31.5
Nominal Product Height (mm)	32.5
Cutout Dimensions (W x L in mm or Diameter in mm)	4000
Weight (kg)	3.392

Packaging

Single packaging type	Carton
Product EAN number	6410014506049
Packaging single length / height (cm)	400.4
Packaging single width (cm)	3.2
Packaging single depth (cm)	3.3
DUN14 (outer)	06410014506049
Units per outer package	1
Packaging outer length / height (cm)	400.4
Packaging outer width (cm)	3.2
Packaging outer depth (cm)	3.3

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes

TECHNICAL DRAWINGS

