

ToLEDo Retro Ball Dimmable ToLEDo RT BALL V2 CL DIM 470LM 827 B22 S 0027480



Product features

· Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps • Same look, size and functionality as incandescent lamps. • The combination of innovative filament chip technology and dimming functionality make it an ideal solution for both hospitality application and for general lighting. • Suitable for replacement of 40W incandescent lamp. • A++ energy rating - 104 Im/W • Dimming functionality helps to vary lighting scene as lamps can be dimmed from 100% to 10% and reduces energy consumption as well. • Sparkling light output. • Omnidirectional light distribution. • Environment friendly - no mercury and lower CO2 emissions. • Dimmable on approved dimmers. • Color temperature - 2700K Homelight









PRODUCT OVERVIEW

Product name	ToLEDo RT BALL V2 CL DIM 470LM 827 B22 S
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Round/globe
Туре	ToLEDo Retro Ball Dimmable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Warranty	3 years
Luminous flux (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	320
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288274805

DATA TABLE

General data	
Product name	ToLEDo RT BALL V2 CL DIM 470LM 827 B22 S
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Round/globe
Туре	ToLEDo Retro Ball Dimmable
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	45
ETIM Class	EC001959
Warranty	3 years



ToLEDo Retro Ball Dimmable ToLEDo RT BALL V2 CL DIM 470LM 827 B22 S 0027480


Luminous flux (Im) 470 Luminous flux (Rated) (Im) 470 Colour temperature (K) 2700 Light colour Homelight Colour Code 827 CRI (Ra) 80 Adjustable chromaticity N Beam Angle (°) 320 Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) (s)	
Luminous flux (Rated) (Im) 470 Colour temperature (K) 2700 Light colour Homelight Colour Code 827 CRI (Ra) 80 Adjustable chromaticity N Beam Angle (°) 320 Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Colour temperature (K) 2700 Light colour Homelight Colour Code 827 CRI (Ra) 80 Adjustable chromaticity N Beam Angle (°) 320 Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Light colour Colour Code 827 CRI (Ra) 80 Adjustable chromaticity N Beam Angle (°) 320 Electrical data Wattage (W) Starting time (max) (s) Warm-up time to 60% of full light (max) 1	
CRI (Ra) 80 Adjustable chromaticity N Beam Angle (°) 320 Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Adjustable chromaticity Beam Angle (°) Starting time (max) (s) Warm-up time to 60% of full light (max) N 320 4.5 Starting time (max) (s) 0.5	
Beam Angle (°) 320 Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Electrical data Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Wattage (W) 4.5 Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Starting time (max) (s) 0.5 Warm-up time to 60% of full light (max) 1	
Warm-up time to 60% of full light (max) 1	
Mains voltage (V) 220-240V~	
Product Voltage (V) 230	
Lamp power factor 0.8	
No. Of switching cycles before premature >50000	
failures	
Transformer required Yes	
Lamp Energy Label (class) F	
kWh per 1000 hours burning time 5	
Nominal Frequency (Hz) 50/60Hz	
Lifetime data	
Average life (Nominal) (h) 15000	
Average life (Rated) (h) 15000	
Physical data	
Nominal Product Length (mm) 83	
Nominal Product Diameter (mm) 45	
Weight (kg) 0.016	
Packaging	
Single packaging type Carton	
Product EAN number 5410288274805	
Packaging single length / height (cm) 9.5	
Packaging single width (cm) 4.8	
Packaging single depth (cm) 4.8	
DUN14 (inner) 25410288274809	
Units per inner package 6	
Packaging inner length / height (cm) 15.6	
Packaging inner width (cm) 10.6	
Packaging inner depth (cm) 11.5	
DUN14 (outer) 15410288274802	
Units per outer package 60	
Packaging outer length / height (cm) 55.5	
Packaging outer width (cm) 33.1	





ToLEDo Retro Ball Dimmable ToLEDo RT BALL V2 CL DIM 470LM 827 B22 S 0027480

Packaging outer depth (cm)	14.5
Safety data	
Odicty data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY







TECHNICAL DRAWINGS

