


Beacon LED Projector - Iris

Beacon Muse Iris Projector O/B 3000K Single Circuit Track - White
2055160



Product features

- Beacon Projector offers precision light exactly where it is needed. The Iris Projector has an adjusting lever to create a perfect circle of light in the required size. High colour rendering CRI 97 typical. IR/UV free light source without heat radiation. LED technology provides an energy efficient solution with reduced maintenance costs.



PRODUCT OVERVIEW

| | |
|---------------------------------|---|
| Product name | Beacon Muse Iris Projector O/B 3000K Single Circuit Track - White |
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Interior |
| General application | Hospitality, Museums & Galleries, Retail |
| ETIM Class | EC001744 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | - |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 97 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 10 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 26 |
| Product Voltage (V) | 240 |
| Electrical protection | Class I |
| Control gear mounting | Integral |
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Product EAN number | 5025768551606 |
| Light source included | INTEGRATED LED |

DATA TABLE

General data

| | |
|--------------|---|
| Product name | Beacon Muse Iris Projector O/B 3000K Single Circuit Track - White |
| Technology | LED |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Interior |

Beacon LED Projector - Iris

Beacon Muse Iris Projector O/B 3000K Single Circuit Track - White
2055160

| | |
|---------------------|--|
| General application | Hospitality, Museums & Galleries, Retail |
| ETIM Class | EC001744 |
| Warranty | 5 years |

Optical data

| | |
|---------------------------------|------------|
| Fixture luminous flux (lm) | - |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 97 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Adjustable chromaticity | N |
| Beam Angle (°) | 10 |
| Distribution type | Adjustable |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|-----------------------------|----------|
| Total power consumption (W) | 26 |
| Mains voltage (V) | 230V~ |
| Product Voltage (V) | 240 |
| Electrical protection | Class I |
| Control gear mounting | Integral |
| Transformer required | Yes |
| Nominal Frequency (Hz) | 50/60Hz |

Lifetime data

| | |
|------------------|-------|
| Lifespan L70 B50 | 50000 |
|------------------|-------|

Physical data

| | |
|-------------------------------|-------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK02 |
| Nominal Product Width (mm) | 185 |
| Nominal Product Height (mm) | 215 |
| Nominal Product Diameter (mm) | 80 |
| Weight (kg) | 1.365 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5025768551606 |
| Packaging single length / height (cm) | 32.0 |
| Packaging single width (cm) | 15.5 |
| Packaging single depth (cm) | 13.0 |
| DUN14 (outer) | 05025768551606 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 32.0 |
| Packaging outer width (cm) | 15.5 |
| Packaging outer depth (cm) | 13.0 |

Beacon LED Projector - Iris

Beacon Muse Iris Projector O/B 3000K Single Circuit Track - White

2055160

TECHNICAL DRAWINGS

