

ToLEDo Superia T5 ECG TOLEDO SUPERIA T5 HE 5FT 2800LM 865 0029512



Product features

60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 35W 1449mm fluorescent triphosphor T5 lamp. High switching cycles - 200,000X. High lumen efficacy -151lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.





PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HE 5FT 2800LM 865
Technology	LED
Watt (Rated) (W)	18.5
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4740609
E-number SE	8293582
Warranty	5 years
Luminous flux (Im)	2800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	18.5
Product Voltage (V)	80
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295121